

(19)



JAPANESE PATENT OFFICE

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **07268605 A**(43) Date of publication of application: **17.10.95**

(51) Int. Cl.

**C23C 14/06**  
**C23C 14/56**  
**C23C 14/58**  
**C23C 28/02**

(21) Application number: **06058625**(22) Date of filing: **29.03.94**(71) Applicant: **NISSHIN STEEL CO LTD**

(72) Inventor: **SAKAMOTO KAZUYUKI**  
**FUKUI YASUSHI**  
**MATSUNO MASANORI**  
**TANAKA HIROSHI**  
**ARIYOSHI YASUMI**  
**SAITO MINORU**

**(54) PRODUCTION OF ALLOYED ZN-MG VAPOR  
 DEPOSITION-COATED STEEL SHEET**

(57) Abstract:

**PURPOSE:** To obtain an alloyed Zn-Mg vapor deposition-coated steel sheet with Fe diffused to the surface of a plating layer and excellent in workability and corrosion resistance.

**CONSTITUTION:** A continuously traveled steel strip with the surface cleaned is introduced into a vacuum chamber, in a reducing or inert atmosphere, deposited with Mg at  $\cong 100^{\circ}\text{C}$  and then with Zn. An alloying heat treatment is applied to the strip immediately after leaving the

vacuum chamber at  $330-600^{\circ}\text{C}$  for  $\leq 10\text{sec}$  in an inert atmosphere or in the atmosphere so that the Fe is diffused from the substrate steel to the plating layer surface. The Zn-plated strip is held at  $200-400^{\circ}\text{C}$  for 1-25hr by using a heating furnace independent of the vacuum chamber to apply alloying heat treatment. Otherwise, the strip before Mg vapor deposition is kept at  $\cong 100^{\circ}\text{C}$ , the temp. is controlled so that the Zn-deposited strip is kept at  $330-500^{\circ}\text{C}$ , and alloying heat treatment is conducted by the sensible heat of the strip.

COPYRIGHT: (C)1995,JPO